



SCC-B5351G / SCC-B5351GP

Vari-Focal Fixed Dome Color Digital Camera

Features

- DSP (Digital Signal Processor)
- 1/3" NTSC : 410,000 / PAL : 470,000 pixels super HAD CCD
- Horizontal resolution (480 TV Lines)
- Lens : f = 3.4 ~ 9mm auto iris
- Back light compensation circuitry
- External synchronization with line-lock
- Power input (AC24V/DC12V compatible)
- Built-in ground fault isolation transformer

Dimensions (unit : mm)



Specifications

		SCC-B5351(G)	SCC-B5351(G)P
Camera Type	Color		Color
Image	Device		Super-HAD CCD
	Size		1/3 inch
	Pixels - Total	811 x 508	795 x 596
	Pixels - Effective	768 x 494	752 x 582
Scanning	System		Interlace
	Horizontal Frequency-Internal Mode	15,734 Hz	15,625 Hz
	Horizontal Frequency-Line-lock Mode	15,750Hz	15,625 Hz
	Vertical Frequency-Internal Mode	5994 Hz	50 Hz
	Vertical Frequency-Line-lock Mode	60 Hz	50 Hz
Min. scene Illumination	Color		0.3 Lux
PAN/TILT	Range-Panning		345° (Manual)
	Range-Tilting		90° (Manual)
Functions	BLC		On
	AGC		On
	FLK		Off/On
	Line Lock		Off/On
	White Balance		ATW
Resolution	Horizontal		480 TV Lines
	Vertical		350 TV Lines
Video Output	VBS 1.0Vp-p		VBS 1.0Vp-p
S/N Ratio	S/N Ratio		50dB
Lens	Focal Length		3.4-9 mm
	Aperture Ratio		F16(Wide), F2.4(Tele)
	Viewing Angle-Tele		31° (H) x 23° (V)
	Viewing Angle-Wide		83° (H) x 62° (V)
	Lens Drive Type		AI (DC)
Environmental Conditions	Operating Temperature		-10° C ~ +50° C
	Humidity		Less than 90%
Power	Power Requirement	AC24V(60Hz)±10% / DC12V+10%/ -5%	AC24V(50Hz)±10% / DC12V+10%/ -5%
	Power Consumption		3W
Physical Specification	Dimensions(ø x H)-Net		118(ø) x 100(H) mm
	Weight-Net		250g
	Loading Quantity(20/40ft)		4,080 / 8,160
	Etc.-Body Color	B5351 : Black / B5351G : White	B5351P : Black / B5351GP : White
	Packing		587 x 435 x 359 mm

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model