



SCC-C6475 / SCC-C6475P

IP Smart Dome Camera with WDR, X22 Zoom and Day&Night

Features

- 1/4" Ex-view P/S 410K CCD
- Built-in X22 optical zoom lens (X10 D-Zoom)
- 360° endless PAN (Slip-ring)
- Remote control : RS-485, RS-422
- 10/100 base-T (RJ-45)
- Support various network protocol(HTTP, FTP, SMTP, TCP, UDP, IP, DHCP, DNS, ARP, NTP, PPPoE, DDNS, RTP, RTSP)
- 480 TV lines of horizontal resolution
- Sensitivity : 0.2 lux (X4 sens-up, color)
- Preset speed : pan (400° /sec), tilt (200° /sec)
- MPEG4 and MJPEG, max. 25fps (@VGA)

Dimensions (unit : mm)



Rear Panel



Specifications

		SCC-C6475(P)	
Camera Section		Same as SCC-C6405(P)	
Pan/Tilt Section		Same as SCC-C6405(P)	
Network Section		Same as SCC-C6405(P)	
Environment	Server	OS	Embedded Linux : Support
	Client	OS	Win 2k/XP : Support
		CPU	PentiumIII 1GHz Higher
		Memory	Memory : 256Mb Higher
		Graphic Accelerator	DirectX 8.1 hijger
Browser	Web browser		Internet explorer 5.0 higher
Compression	MPEG4 / MJPEG		do not support simultaneous operation
Hardware	Flash memory		8 Mbyte
	OS		embedded Linux
	SDRAM		32Mbyte
	Power Source		84V DC,500mA (using the supplied AC adapter)
	Ambient Operating Temperature		0C - +40C (32F - 104F) degree
	Dimensions		93 mm (H) x 61 mm (W) x 43 mm (D)
Network	Ethernet		10/100BaseT
	Network Protocol	Network Protocol	DHCP, TCP/IP, UDP/IP, HTTP, FTP, SMTP, RTP/RTSP, NTP, PPPoE
		DDNS	Notification Support for Dynamic IP
		ADSL	Only PPPoE Support
		Cable Modem	DHCP Support
		Video transfer protocol	TCP, UDP (Multicast, Unicast) support
Video Resolution	NTSC	VGA	640x480
	PAL	VGA	640x480
Video Quality	Quality		High, Midium, Low
Performance	MJPEG	VGA	Max 25 fps
	MPEG4	VGA	Max 25 fps
Connection Users	MJPEG	Multicast	Max - 10 Users
	MPEG4	Multicast	Max - 20 Users
Alarm Control			MJPEG only support (MPEG4 is not supported)
		FTP, SMTP	On alarm, Image will be sent by FTP SMTP
	Pre-Alarm		Max Total 60 images
	Post-Alarm		Max Total 60 images
Recording	Recording		Max 10min recordcan be recorded when PC Hard Disk available space is bigger than 20% of total space
IP Notification		FTP, SMTP	The ip address is sent by FTP and (or) SMTP, when a dynamic ip is received
IP Installer		IP address Installation	IP installation function (XP, win 2000 support)
Software Upgrade		Firmware Upgrade	Firmware upgrade by web browser
Access Level		Login Access Level	Guest, Administrator, Operator, User
Security		IP Filtering	IP filtering
Time Setting		Time Setting	Setting by a NTP server on the internet
PTZ Control		Pan/Tilt/Zoom control	Auto pan, preset, scan function support
Sequence		Sequence	1CH/ 4Ch sequence support
Language		Language	English Only
ETC Section			
Power Source			24 V AC, 60 Hz or 50 Hz
Power Consumption			20 W
Ambient Operating Temperature			-10°C to +50°C (14°F to 122°F)
Dimensions			DOME : 147 (ø), Outline : 159.6 (ø) x 177(H) (Adapter:23.5(H)mm)
Weight			approx. 1.7 kg

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model